

Alu-Ramp Light Range

Without edge

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	Weight of ramp pair kg
		500	750	1000				
500	H 030/15	1180	1575	1800	595	1500	200	10
600	H 030/20	775	930	1160	445	2000	200	13
800	H 030/25	565	650	755	350	2500	200	16
900	H 030/30	440	490	550	290	3000	200	20
1100	H 030/35	355	385	425	245	3500	200	23
1200	H 030/40	290	310	340	240	4000	200	26

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	Internal width mm	External width mm	Weight of ramp pair kg
		750	1000	1250					
500	H 50/15S	2250	2250	2250	900	1500	250	320	18
600	H 50/20S	1800	2250	2250	900	2000	250	320	24
800	H 50/25S	1500	1800	2250	750	2500	250	320	30
900	H 50/30S	1200	1380	1587	750	3000	250	320	36
1100	H 50/35S	950	1050	1160	450	3500	250	320	42
1200	H 50/40S	750	825	900	450	4000	250	320	48

500	H 50/15SL	2250	2250	2250	900	1500	300	370	20
600	H 50/20SL	1800	2250	2250	900	2000	300	370	26
800	H 50/25SL	1500	1800	2250	750	2500	300	370	32
900	H 50/30SL	1200	1380	1587	750	3000	300	370	38
1100	H 50/35SL	950	1050	1160	450	3500	300	370	44
1200	H 50/40SL	750	852	900	450	4000	300	370	50

Height of loading level mm	Item code	Ramp pair loading capacity			Concentrated Load	Length mm	External width mm	Weight of ramp pair kg
		750	1000	1250				
500	H 60/15S	1750	1750	1750	1750	1500	300	19
600	H 60/20S	1700	1700	1700	1500	2000	300	25
800	H 60/25S	1650	1700	1700	1500	2500	300	30
900	H 60/30S	1250	1405	1610	1430	3000	300	36
1100	H 60/35S	990	1090	12515	1220	3500	300	41